

Draagvermogen **IPN BALKEN**

Maximum toelaatbare gelijkmatig verdeelde belasting in kg.

De cijfers gelden voor een balk, vrij opgelegd aan de uiteinden, rekening houdend met het eigen gewicht.

Maximum materiaalspanning 12kN/cm²

IPN	GEW KG/M	BOOSCHOTSE METALEN nv Overspanning in meters															IPN
		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
80	6,1	610	260	130													80
100	8,5	1350	580	310	180												100
120	11,4	2600	1140	610	370	220	130										120
140	14,6	3900	2010	1100	670	430	270	170									140
160	18,3	5580	3300	1810	1110	730	490	330	210								160
180	22,4	7680	5080	2830	1760	1170	800	550	380	250							180
200	26,7	10200	6770	4210	2630	1760	1220	870	620	430	280						200
220	31,7	13300	8800	6040	3800	2550	1800	1290	940	680	470	310					220
240	36,9	16900	11200	8350	5300	3590	2540	1850	1360	1010	740	520					240
260	42,7	21100	14000	10440	7200	4890	3490	2560	1910	1430	1070	780	550				260
280	48,9	25900	17200	12800	9550	6510	4660	3440	2590	1970	1490	1120	830	580			280
300	55,3	31200	20700	15400	12300	8450	6070	4500	3410	2620	2020	1550	1170	860	590		300
320	62,6		24800	17500	14700	10800	7810	5820	4430	3420	2660	2070	1590	1200	880	600	320
340	69,3		29300	21900	17400	13600	9850	7360	5640	4380	3440	2700	2110	1630	1230	890	340
360	77,6		34600	25800	20500	17000	12370	9270	7120	5560	4340	3480	2750	2160	1670	1250	360
380	85,6		40100	29900	23800	19700	15220	11430	8800	6900	5480	4360	3490	2770	2180	1680	380
400	94,2		46700	34700	27600	22800	18600	14000	10800	8480	6760	5420	4370	3610	2800	2200	400
450	116,2			48500	38600	31900	27200	22200	17200	13600	10900	8880	7250	5930	4840	3930	450
500	142,4			65400	52100	43100	36700	31900	26100	20800	16800	13700	11300	9330	7730	6400	500
550	168,7				68500	56800	48300	42000	37000	30300	24600	20200	16700	14000	11700	9820	550

Max.doorbuiging = lengte/500